


D300 Plastic Delivery Spool

Packaging Specification

DATA SHEET



AT A GLANCE

Product code	D300
Construction	Cylindrical barrel
Standard material	Recycled industrial ABS
Standard colour	Black
Nominal tare mass	685 g
Winding volume	3,304 or 4,072 cm3

NOMINAL DIMENSIONS

Ref.	Dimension	Value
d1	Flange diameter	300 mm
d2	Barrel diameter	208 or 180 mm
d3	Bore diameter	51.5 mm
d4	Bore recess	10 mm
L1	Overall width	103 mm
L2	Traverse width	90 mm
e1	Drive-hole PCD	44.5 mm

WIRE SUPPLY GUIDANCE

TYPICAL WIRE DIAMETER

0.70 - 2.20 mm

Application dependent - confirm at quotation stage

TYPICAL MAXIMUM FILL

Up to 15 kg

Varies by alloy density, temper, winding tension and pattern

Suitable WintWire products

- Stainless and spring steel
- Nickel and cobalt alloys
- Copper alloys and titanium

HIGH RIGIDITY

Stable flange geometry

SMOOTH PAY-OFF

Controlled unwinding

TRACEABLE SUPPLY

Order and batch labels

EXPORT READY

Protective packing options

Document WW-PS-D300 | Revision: V1.0 | Nominal data. Final spool suitability and fill weight must be confirmed at quotation stage.

WintWire Ltd

Manufacturers of speciality round, flat and profile wires
www.wintwire.co.uk

REQUEST A QUOTATION

sales@wintwire.co.uk