


DIN125 Plastic Delivery Spool

Packaging Specification

DATA SHEET



AT A GLANCE

Product code	DIN125
Construction	Cylindrical barrel
Standard material	Recycled industrial ABS
Standard colour	Black
Nominal tare mass	200 g
Winding volume	725 cm ³

NOMINAL DIMENSIONS

Ref.	Dimension	Value
d1	Flange diameter	125 mm
d2	Barrel diameter	80 mm
d3	Bore diameter	16 mm
d4	Bore recess	24 mm
d5	Drive hole	7 mm
d6	Wire hole	3 mm
L1	Overall width	125 mm
L2	Traverse width	100 mm
e1	Drive-hole PCD	20 mm

WIRE SUPPLY GUIDANCE

TYPICAL WIRE DIAMETER

0.19 - 0.55 mm

Application dependent - confirm at quotation stage

TYPICAL MAXIMUM FILL

Up to 3 kg

Varies by alloy density, temper, winding tension and pattern

Suitable WintWire products

- Stainless and spring steel
- Nickel and cobalt alloys
- Copper alloys and titanium

HIGH RIGIDITY

Stable flange geometry

SMOOTH PAY-OFF

Controlled unwinding

TRACEABLE SUPPLY

Order and batch labels

EXPORT READY

Protective packing options

Document WW-PS-DIN125 | Revision: V1.0 | Nominal data. Final spool suitability and fill weight must be confirmed at quotation stage.

WintWire Ltd

Manufacturers of speciality round, flat and profile wires
www.wintwire.co.uk

REQUEST A QUOTATION

sales@wintwire.co.uk