


DIN160 Plastic Delivery Spool

Packaging Specification

DATA SHEET



AT A GLANCE

Product code	DIN160
Construction	Cylindrical barrel
Standard material	Recycled industrial ABS
Standard colour	Black
Nominal tare mass	250 g
Winding volume	1,568 cm ³

NOMINAL DIMENSIONS

Ref.	Dimension	Value
d1	Flange diameter	160 mm
d2	Barrel diameter	100 mm
d3	Bore diameter	22 mm
d4	Bore recess	34 mm
d5	Drive hole	13 mm
d6	Wire hole	3 mm
L1	Overall width	160 mm
L2	Traverse width	128 mm
e1	Drive-hole PCD	32 mm

WIRE SUPPLY GUIDANCE

TYPICAL WIRE DIAMETER

0.25 - 0.71 mm

Application dependent - confirm at quotation stage

TYPICAL MAXIMUM FILL

Up to 5 kg

Varies by alloy density, temper, winding tension and pattern

Suitable WintWire products

- Stainless and spring steel
- Nickel and cobalt alloys
- Copper alloys and titanium

HIGH RIGIDITY

Stable flange geometry

SMOOTH PAY-OFF

Controlled unwinding

TRACEABLE SUPPLY

Order and batch labels

EXPORT READY

Protective packing options

Document WW-PS-DIN160 | Revision: V1.0 | Nominal data. Final spool suitability and fill weight must be confirmed at quotation stage.

WintWire Ltd

Manufacturers of speciality round, flat and profile wires
www.wintwire.co.uk

REQUEST A QUOTATION

sales@wintwire.co.uk