


# DIN250 Plastic Delivery Spool

Packaging Specification

DATA SHEET



## AT A GLANCE

|                   |                         |
|-------------------|-------------------------|
| Product code      | DIN250                  |
| Construction      | Cylindrical barrel      |
| Standard material | Recycled industrial ABS |
| Standard colour   | Black                   |
| Nominal tare mass | 1,050 g                 |
| Winding volume    | 4,637 cm <sup>3</sup>   |

## NOMINAL DIMENSIONS

| Ref. | Dimension       | Value       |
|------|-----------------|-------------|
| d1   | Flange diameter | 250 mm      |
| d2   | Barrel diameter | 160 mm      |
| d3   | Bore diameter   | 22 or 36 mm |
| d4   | Bore recess     | 34 mm       |
| d5   | Drive hole      | 13 mm       |
| d6   | Wire hole       | 4 mm        |
| L1   | Overall width   | 200 mm      |
| L2   | Traverse width  | 160 mm      |
| e1   | Drive-hole PCD  | 32 mm       |

## WIRE SUPPLY GUIDANCE

### TYPICAL WIRE DIAMETER

**0.40 - 1.50 mm**

Application dependent - confirm at quotation stage

### TYPICAL MAXIMUM FILL

**Up to 20 kg**

Varies by alloy density, temper, winding tension and pattern

### Suitable WintWire products

- Stainless and spring steel
- Nickel and cobalt alloys
- Copper alloys and titanium

### HIGH RIGIDITY

Stable flange geometry

### SMOOTH PAY-OFF

Controlled unwinding

### TRACEABLE SUPPLY

Order and batch labels

### EXPORT READY

Protective packing options

Document WW-PS-DIN250 | Revision: V1.0 | Nominal data. Final spool suitability and fill weight must be confirmed at quotation stage.

## WintWire Ltd

Manufacturers of speciality round, flat and profile wires  
www.wintwire.co.uk

## REQUEST A QUOTATION

sales@wintwire.co.uk