


DIN355 Plastic Delivery Spool

Packaging Specification

DATA SHEET



AT A GLANCE

Product code	DIN355
Construction	Cylindrical barrel
Standard material	Recycled industrial ABS
Standard colour	Black
Nominal tare mass	1,850 g
Winding volume	9,531 cm ³

NOMINAL DIMENSIONS

Ref.	Dimension	Value
d1	Flange diameter	355 mm
d2	Barrel diameter	224 mm
d3	Bore diameter	36 mm
d4	Bore recess	60 mm
d5	Drive hole	26 mm
d6	Wire hole	5 mm
L1	Overall width	200 mm
L2	Traverse width	160 mm
e1	Drive-hole PCD	80 mm

WIRE SUPPLY GUIDANCE

TYPICAL WIRE DIAMETER

1.00 - 3.00 mm

Application dependent - confirm at quotation stage

TYPICAL MAXIMUM FILL

Up to 40 kg

Varies by alloy density, temper, winding tension and pattern

Suitable WintWire products

- Stainless and spring steel
- Nickel and cobalt alloys
- Copper alloys and titanium

HIGH RIGIDITY

Stable flange geometry

SMOOTH PAY-OFF

Controlled unwinding

TRACEABLE SUPPLY

Order and batch labels

EXPORT READY

Protective packing options

Document WW-PS-DIN355 | Revision: V1.0 | Nominal data. Final spool suitability and fill weight must be confirmed at quotation stage.

WintWire Ltd

Manufacturers of speciality round, flat and profile wires
www.wintwire.co.uk

REQUEST A QUOTATION

sales@wintwire.co.uk