


WD560 Wooden Delivery Reel

Packaging Specification

DATA SHEET



AT A GLANCE

Product code	WD560
Construction	Wooden reel, plywood flanges
Standard material	Birch plywood
Standard colour	Natural wood
Returnable	Yes
Max carrying weight	150 kg

NOMINAL DIMENSIONS

Ref.	Dimension	Value
d1	Flange diameter	560 mm
d2	Barrel diameter	315 mm (PVC tube)
d3	Bore / centre hole	56 mm
d5	Drive hole	25 mm
L2	Traverse width	280 mm

WIRE SUPPLY GUIDANCE

TYPICAL WIRE DIAMETER

0.30 - 6.00 mm

Application dependent - confirm at quotation stage

MAX CARRYING WEIGHT

Up to 150 kg

Varies by alloy density, temper, winding tension and pattern

Suitable WintWire products

- Stainless and spring steel
- Nickel and cobalt alloys
- Copper alloys and titanium

HIGH RIGIDITY

Stable flange geometry

SMOOTH PAY-OFF

Controlled unwinding

TRACEABLE SUPPLY

Order and batch labels

EXPORT READY

Protective packing options

Document WW-PS-WD560 | Revision: V1.0 | Nominal data. Final reel suitability and carrying weight must be confirmed at quotation stage.

WintWire Ltd

Manufacturers of speciality round, flat and profile wires
www.wintwire.co.uk

REQUEST A QUOTATION

sales@wintwire.co.uk